



RIME

98PRIME10
98PRIME30
98PRIME50



RIME SENSOR

98PRIME10SEN
98PRIME20SEN
98PRIME30SEN
98PRIME50SEN



RIME / RIME SENSOR STELLAR

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Energy class
98PRIME10	10	700	5000-5500K	black	85	35	115	A++A
98PRIME20	20	1400	5000-5500K	black	-	-	-	A++A
98PRIME30	30	2100	5000-5500K	black	140	45	180	A++A
98PRIME50	50	3500	5000-5500K	black	185	50	225	A++A
98PRIME150	150	10500	5000-5500K	black	325	85	400	A++A
98PRIME200	200	14000	5000-5500K	black	325	85	400	A++A
98PRIME10SEN	10	700	5000-5500K	black	100	50	230	A++A
98PRIME20SEN	20	1400	5000-5500K	black	145	55	300	A++A
98PRIME30SEN	30	2100	5000-5500K	black	190	60	340	A++A
98PRIME50SEN	50	3500	5000-5500K	black	245	70	420	A++A

Body: Aluminium casting | LED driver: mounted in the body | Light source: Epistar SMD2835 | Input voltage: 176- 264V | Ambient Temperature: -20°C+ +55°C

